

2006 International Residential Code Study Companion

Errata to First Printing

Study Session 1, page 19, Quiz, #5. c. violate ~~modify~~ (posted 5/1/07)

Study Session 1, page 19, Quiz, #7. b. for ~~or~~ individual cases where the strict letter of the code is impractical (posted 5/1/07)

Study Session 1, page 25, Quiz, #33. Which of the following reasons is not specifically ~~specieally~~ identified by the code as authority to suspend or revoke a permit? (posted 5/1/07)

Study Session 2, page 49, Quiz, #21. ~~What is the minimum distance~~ A roof projection on a dwelling shall be located a minimum of _____ from an interior lot line. (posted 5/1/07)

Study Session 2, page 49 Quiz, #23. Exterior wall openings located less than 3 feet from an interior lot line shall be protected with what minimum fire protection rating? (posted 5/1/07)

Study Session 7, page 183, Quiz, #32. For a building located in ~~is~~ Seismic Design Category D₀, plate washers used in the connection of braced wall line sills to a concrete foundation shall be a minimum of _____ in size. (posted 5/1/07)

Study Session 8, page 204, Quiz, #1. a. 2 feet; c. 4 feet (posted 5/1/07)

Study Session 18, page 449, IRC E4103.4. Where an existing luminaire is located within 5 feet of a pool, spa, or hot, it need only be located at least 12 ~~5~~ feet above the maximum water level if the luminaire is securely attached to the existing support and GFCI protection is provide on the luminaire's branch circuit. (posted 5/1/07)

Answer Key, Study Session 2, page 460, #23. Table R302.12 (posted 5/1/07)

Answer Key, Study Session 10, page 468, #31. Section M13054.1.3, Exception 2 (posted 5/1/07)

Study Session 15, page 368, IRC P2903.1, P2903.2. The water service and water distribution systems shall be designed and pipe sizes shall be selected such that under conditions of peak demand, the capacities at the point of outlet discharge shall not be less than shown in Table P2903.1. The maximum water consumption flow rates and quantities for all plumbing fixtures and fixture fittings shall be in accordance with Table P2903.2. Atties containing appliances requiring access shall be provided with an opening and a clear and unobstructed passageway large enough to allow removal of the largest appliance, but not less than 30 inches (762 mm) high and 22 inches (559 mm)

~~wide and not more than 20 feet (6096 mm) in length when measured along the centerline of the passageway from the opening to the appliance.~~ (posted 2/25/08)

Study Session 1, page 10, IRC R105.1, R105.2. Work exempt from building permit:

- Water tanks supported directly on grade, if the capacity does not exceed 5,000 gallons and ratio of height to diameter or width does not exceed 2 to 1 (posted 3/12/08)