

2009 International Residential Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1 st through 5 th PRINTING (Posted: 12-06-2011)

CHAPTER 5 FLOORS

R502.1.1 Preservative-treated lumber. Preservative treated dimension lumber shall also be identified as required by Section ~~R319.1~~ R317.2.

2009 International Residential Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1st and 2nd PRINTING (JULY 14, 2011)

CHAPTER 5 FLOORS

TABLE R503.2.1.1(1)

ALLOWABLE SPANS AND LOADS FOR WOOD STRUCTURAL PANELS FOR ROOF AND SUBFLOOR SHEATHING
AND COMBINATION SUBFLOOR UNDERLAYMENT^{a,b,c}

SPAN RATING	MINIMUM NOMINAL PANEL THICKNESS (Inch)	ALLOWABLE LIVE LOAD (psf) ^{h,i}		MAXIMUM SPAN (inches)		LOAD (pounds per square foot, at maximum span)		MAXIMUM SPAN (inches)
		SPAN @ 16" o.c.	SPAN @ 24" o.c.	With edge support ^d	Without edge support	Total load	Live load	
Sheathing ^e				Roof ^f				Subfloor ^j
48/24	23/32, 3/4-3/4	-	175	48	36	45	35	24