

2012 International Building Code

Errata

(Portions of text and tables not shown are unaffected by the errata)

SECOND PRINTING (Updated May 23, 2012)

CHAPTER 17 SPECIAL INSPECTIONS AND TESTS

1704.5 Structural observations. Where required by the provisions of Section 1704.5.1 or 1704.5.2, the owner shall employ a *registered design professional* to perform structural observations as defined in Section 4702 ~~202~~.

Prior to the commencement of observations, the structural observer shall submit to the *building official* a written statement identifying the frequency and extent of structural observations.

At the conclusion of the work included in the permit, the structural observer shall submit to the *building official* a written statement that the site visits have been made and identify any reported deficiencies which, to the best of the structural observer's knowledge, have not been resolved.

TABLE 1705.3 REQUIRED VERIFICATION AND INSPECTION OF CONCRETE CONSTRUCTION

In rows 3 and 4, under "REFERENCED STANDARD" COLUMN change Section reference ~~21-2.8~~ 21.1.8

1705.7 Driven deep foundations. *Special inspections* shall be performed during installation and testing of driven deep foundation elements as required by Table 1705.7. The *approved instruction* geotechnical report ~~and the construction~~ documents prepared by the *registered design professionals*, shall be used to determine compliance.

1705.11.6 Mechanical and electrical components. *Special inspection* for mechanical and electrical components shall be as follows:

1. Periodic special inspection is required during the anchorage of electrical equipment for emergency or and standby power systems in structures assigned to *Seismic Design Category C, D, E or F*;
(No changes to Items 2 through 5)

1705.11.7 Storage racks. Periodic *special inspection* is required ~~during for~~ the anchorage of storage racks 8 feet (2438 mm) or greater in height in structures assigned to *Seismic Design Category D, E or F*.