

2012 International Plumbing Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1st through 4th PRINTING (June 24, 2014)

CHAPTER 4 FIXTURES, FAUCETS AND FIXTURE FITTINGS

[B] 410.2 Minimum number. Where drinking...

Exception~~s~~:

1. A single drinking fountain.....
2. Where drinking fountains are primarily for children's use, the drinking fountains for people using wheelchairs shall be permitted to comply with the children's provisions in ICC A117.1 and drinking fountains for standing children shall be permitted to provide the spout at 30 inches (762 mm) minimum above the floor.

2012 International Plumbing Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1st and 2nd PRINTING (September 14, 2012)

CHAPTER 4 FIXTURES, FAUCETS AND FIXTURE FITTINGS

403.5 Drinking fountain location. Drinking fountains....500 feet (152 400 mm) of the...

2012 International Plumbing Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1st and 2nd PRINTING (September 13, 2012)

CHAPTER 4 FIXTURES, FAUCETS AND FIXTURE FITTINGS

410.1 Approval. Drinking fountains shall conform to ASME A112.19.1/CSA B45.2 or ASME A112.19.2/CSA B45.1 and water coolers shall conform to ~~ARI~~ AHRI 1010.

2012 International Plumbing Code Errata

(Portions of text and tables not shown are unaffected by the errata)

1st and 2nd PRINTING (June 6, 2012)
--

CHAPTER 4 FIXTURES, FAUCETS AND FIXTURE FITTINGS

Table 403.1

TABLE 403.1 MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES (See Sections 403.~~2~~ 1.1 and 403.~~3~~ 2)

Correction is applicable to title shown on multiple pages.