

2015 International Building Code Errata

(Portions of text and tables not shown are unaffected by the errata)

THIRD PRINTING (Updated April 15, 2020)

APPENDIX H SIGNS

H106.1.1 Internally illuminated signs. Except as provided for in Sections ~~402.16~~ [402.6.4](#) and 2611, where internally illuminated signs have facings of wood or approved plastic, the area of such facing section shall be not more than 120 square feet (11.16 m²) and the wiring for electric lighting shall be entirely enclosed in the sign cabinet with a clearance of not less than 2 inches (51 mm) from the facing material. The dimensional limitation of 120 square feet (11.16 m²) shall not apply to sign facing sections made from flame-resistant-coated fabric (ordinarily known as “flexible sign face plastic”) that weighs less than 20 ounces per square yard (678 g/m²) and that, when tested in accordance with NFPA 701, meets the fire propagation performance requirements of both Test 1 and Test 2 or that, when tested in accordance with an approved test method, exhibits an average burn time of 2 seconds or less and a burning extent of 5.9 inches (150 mm) or less for 10 specimens.

2015 International Building Code Errata

(Portions of text and tables not shown are unaffected by the errata)

FIRST PRINTING (Updated August 11, 2014)

APPENDIX H SIGNS

User note: Code change proposals to this appendix will be considered by the IBC – Structural Code Development Committee during the 2016 (Group B) Code Development Cycle. See explanation on page iv.