FIRST PRINTING (Updated August 11, 2014)

SECTION 307 HIGH-HAZARD GROUP H

[F] TABLE 307.1(2) MAXIMUM ALLOWABLE QUANTITY PER CONTROL AREA OF HAZARDOUS MATERIAL POSING A HEALTH HAZARD ^{a, c, f, h, i}

MATERIAL	STORAGE ^b			USE-CLOSED SYSTEMS ^b			USE-OPEN SYSTEMS ^b	
	Solid pounds	Liquid gallons (pounds) ^{d,f} <u>e</u>	Gas cubic feet at NTP (pounds) ^d	Solid pounds	Liquid gallons (pounds) ^{d, e}	Gas cubic feet at NTP (pounds) ^d	Solid pounds	Liquid gallons (pounds) ^d
Corrosives	5,000	500	Gaseous 810 _{e,f} Liquefied (150)	5,000	500	Gaseous 810 e Liquefied (150)	1,000	100

(Change footnotes in 2nd, 3rd and 6th column heading, and 4th column as indicated. Remainder of table remains unchanged.)

[F] 307.7 High-hazard Group H-5. Semiconductor fabrication facilities and comparable research and development areas in which hazardous production materials (HPM) are used and the aggregate quantity of materials is in excess of those listed in Tables 307.1(1) and 307.1(2) shall be classified as Group H-5. Such facilities and areas shall be designed and constructed in accordance with Section 415.10 405.11.

SECTION 310 RESIDENTIAL GROUP R

310.6 Residential Group R-4. Residential Group R-4 occupancy shall include buildings, structures or portions thereof for more than five but not more than 16 persons, excluding staff, who reside on a 24-hour basis in a supervised residential environment and receive *custodial care*. Buildings of Group R-4 shall be classified as one of the occupancy conditions specified in Section 310.6.1 or 310.6.2. The persons receiving care are capable of self-preservation. This group shall include, but not be limited to, the following:

Alcohol and drug centers Assisted living facilities Congregate care facilities *Group homes* Halfway houses Residential board and care facilities Social rehabilitation facilities

Group R-4 occupancies shall meet the requirements for construction as defined for Group R-3, except as otherwise provided for in this code.