





2

1. Perform hazard review. 2. Perform construction document review. 3. Perform calculations/ specifications review. 4. Perform component and materials review.







5








8





Importance	
The main goal of all plan reviews is to ensure the life safety of the public:	
• Fire	
• Egress • Structural	
• Structural	
2021 BC Performing Structural Plan Reviews Workbook page 9	iGE




11










14










17










20









23










26








29









32









35







38



Step 1. Determine if a geotechnical report required.

- Questionable soil (Section 1803.5.2)
- Expansive soil (Section 1803.5.3)
- Ground-water table (Section 1803.5.4)
- Deep foundations (Section 1803.5.5)
- Rock strata (Section 1803.5.6)
- Excavation near foundations (Section 1803.5.7)
- \bullet Compacted fill material (Section 1803.5.8

40


Step 1. Determine if a geotechnical report required.

- Controlled low-strength material (Section 1803.5.9)
- Alternate setback and clearance (Section 1803.5.10)
- Structure assigned to Seismic Design Category C, D, E or F (Sections 1803.5.11 and 1803.5.12)

Workbook page 35


41

Site Class	V_{5}	N or N _{ch}	S,
A. Hard rock	> 5,000 ft/s	NA	NA NA
B. Rock	2,500 to 5,000 ft/s	NA	NA
C. Very dense soil and soft rock	1,200 to 2,500 ft/s	>50	> 2,000 psf
D. Stiff soil	600 to 1,200 ft/s	15 to 50	1,000 to 2,000 psf
E. Soft clay soil	< 600 ft/s	< 15	< 1,000 psf
	characteristics: Plasticity index PI > : Moisture content w≥ Undrained shear street	40%, and	
F. Soils requiring site response analysis in accordance with Section 21.1	See Section 20.3.1		
Company (Associate Control	Figure 17: Soil Site Classi		14 5 T-LL 20 2 4





44





Discussion of these requirements • Look at page 37-38 and discuss what information is required. • What would be a suitable comment to write if anything was missing? **CC SPRING** **Workbook page 37-38** **Workbook page 37-38**

46

 Section 1603 Construction Document Section 1604.5 Risk Category 	ts
Section 1604.5 Risk Category	C.J
Section 1609.3 Wind Speeds	
Section 1613.2.5 Seismic Design Category	
• Section 1615 Tsunami Loads	
Section 1616 Structural Integrity	
Section 1704.6 Structural Observations	


47






Risk Category from Table 1604.5 of IBC	Snow Importance Factor,	Ice Importance Factor—Thickness,	Ice Importance Factor—Wind,	Seismic Importance Factor,
1.	0.80	0.80	1.00	1.00
- 11	1.00	1.00	1.00	1.00
111	1.10	1.25	1.00	1.25
IV	1.20	1.25	1.00	1.50
Ameri		re 24: Snow Importance F fessional Engineers (ASCE		1.5-2

50





	_	VALUES MARRIED BOX	TABLE 1613.2.3(1) OF SITE COEFFICE TABLETED MAXIMO	ACCOMPLETE SET SAF	Decision for a 1	
SITE CLASS		SPECTRAL RE	SPONSE ACCELERA	TOW PARIAMETER AT	Sough track	
	5, 4 925	5 ₄ = 5.00	5,+976	5; = 5.00 0.6	6,-126	5,111
A.	0.0	0.9	0.9	0.9	0.9	5.9
M -	1.1	-1.5	1.7	12	1.2	1.2
D.	16	1.8	1.2	- 12	10	10
0	24	12	13	No. 2	Nort	
	No. 5					
a. Use analyse than the S. Values shall be done	place by an	Note by reference of suggest of the	Note b probab propose work SCR.7.	Note 8	Nat 9	Note 8
8. Vulner dell for Ann	ordered by provide	VALUES.	SCE 7.	NY F.*	Note 8	
a Une single like inc. 8. Vulner delli fir delli	enter de la continue	VALUES - MARGINET - MA	mind represent with SCL7. SABLE 1813/2/3(2) OF SIFE CORPIES. TARGETED MACHINATORIE ACCELERATIONS	INT F _a *	Note 6	None's
8. Vulner dell for Ann	SA 91	VALUES WALVES SECTION AND AND AND AND AND AND AND AND AND AN	MARKE SATE TOOLS SAIRLE SATE TOOLS SAIRLE SATE TOOLS SATE COMPTICE TANGETED MAXIMUM SATE	NT F,* CONSIDERED EAST & PARABETER AT 1	Note 5 F. Note 18 (1806) Helicolog Mellicolog S, +0.5	Notes
8. Vulner dell for Ann	54.91 0.8	VALUES SAPES OF SERVICES SAPES	WHILE SETTINGS WHILE SETTINGS OF SHE CORPINAT TAMORTO MACOMM OWE ACCULINAT S.+5.5 0.8	INT F ₀ * CONSIDERED EAST R FARMANCES AT 1 S. + 0.6 CS	Side 8 Fy. Substitute (midely substitute of the side of the sid	Note:
8. Vulner dell for Ann	54 91 0.8	VALUE - STATE STAT	PART OF THE PART O	ME F, * CONSIDERED BAR FARABLES AT 1 S. + 54 63	Sole b	Note:
8. Vulner dell for Ann	SA 91	VALUES - SAME 1 A A A A A A A A A	ARLE INTERIOR OF THE CONTROL OF THE	NT F, * COMMITTEE AT B + 0.4 0.3 1.5	Sole b	5,000 6,000
8. Vulner dell for Ann	54 91 0.8	VALUE - STATE STAT	PART OF THE PART O	ME F, * CONSIDERED BAR FARABLES AT 1 S. + 54 63	Sole b	Note:
8. Vulner dell for Ann	SA 91	VALUES - SAME 1 A A A A A A A A A	ARLE INTERIOR OF THE CONTROL OF THE	NT F, * COMMITTEE AT B + 0.4 0.3 1.5	Sole b	5,000 6,000

53


Step 3. Determine the seism category	iic design
$S_{DS} = (2/3)(S_S)(F_A)$	(IBC Equation 16-38)
$S_{D1} = (2/3)(S_1)(F_V)$	(IBC Equation 16-39)
2021 NC Performing Structural Plan Reviews Workbook page 44	CC SPRING WEEKLANGER




ategory			
ategory			
	TABLE 1613.3.50	0	
SEISMIC DESIGN CATEGOR	Y BASED ON SHORT-PERIOD	(0.2 second) RESPONSE ACC	ELERATION
VALUE OF S	lorii	HISK CATEGORY	
S _{in} < 0.167g	A	A	Α.
$0.167g \le S_{ab} < 0.33g$	R	R	C
$0.33g \le S_{10} < 0.50g$	- C-	C	D D
$0.50 g \leq S_{pp}$	D	D	D
RESEASO DESIGN CATE	TABLE 1613,3.5()	2) DEBIOD BESDONSE ACCELE	BATION
		RISK CATEGORY	
VALUE OF S	lord.	· · · · ·	IV.
$S_{pq} < 0.067g$	A.	A	A
$0.067g \le S_{col} < 0.133g$	В	В	C
$0.133g \le S_{po} < 0.20g$	C	C	D
$0.20g \pm S_{fin}$	D	D	D


56

TASK 5 – Verify Win	d Loads
• Section 1609.1.1	Determination of Wind Loads
• Section 1609.3	Ultimate Design Wind Speed (V_{ult})
• Figures 1609.3 (1-3)	Wind Speed for Risk Categories I, II and III-IV
• Section 1609.4	Exposure Category
	Workbook page 45
2021 IBC Performing Structural Plan Reviews	WILLIAM IN THE PROPERTY OF THE





59



Step 3. Determine if proposed structure is located in a wind-borne debris region

- Within 1 mile of the coastal mean high water line where the ultimate design wind speed, Vult, is 130 mph or greater; or
- In areas where the ultimate design wind speed is 140 mph or greater. If the jurisdiction is located within a hurricane-probe region the review must make sure that the project is not located within a wind-borne debris region. If it is, all exterior glazing must shall be impact resistant in accordance with Section 1609.1.2.

61

Step 4. Calculate wind loads


- Chapter 27 of ASCE 7-16: Wind loads on buildings—MWFRS (Directional Procedure)
- Chapter 28 of ASCE 7-16: Wind loads on buildings—MWFRS (Envelope
- Chapter 29 of ASCE 7-16: Wind loads building appurtenances and other structures
- Chapter 30 of ASCE 7-16: Components and cladding
- Chapter 31 of ASCE 7-16: Wind tunnel procedure


62

TASK 6 – Verify Snow Loads

- Section 1608.2 Ground Snow Loads
- Figure 1608.2

Ground Snow Loads for the **United States**





65




Step 2. Verify roof snow load (P_f) $P_f = (0.7)(C_e)(C_t)(I_s)(P_g)$ (Equation 7.3-1, ASCE 7-16)


67

Terrain Category	Fully Exposed	Exposure of Roof' Partially Exposed	Sheltered
B (see Section 26.7 of ASCE 7)	0.9	1.0	1.2
C (see Section 26.7 of ASCE 7)	0.9	1.0	1.1
D (see Section 26.7 of ASCE 7)	0.8	0.9	1.0
Above the treeline in windswept mountainous areas.	0.7	0,8	N/A
In Alaska in areas where trees do not exist within a 2-mile (3 km) radius of the site.	0.7	0.8	N/A


68



Risk Category from Table 1604.5 of IBC	SnowImportance Factor, /,	Ice Importance Factor-Thickness, I,	Ice Importance Factor-Wind, I,,	Seismic Importance Factor,
1	0.80	0.80	1.00	1.00
- 11	1.00	1.00	1.00	1.00
111	1.10	1.25	1.00	1.25
IV	1.20	1.25	1.00	1.50



71





TASK 7 — Review Geologic Hazards Section 1803.3 Section 1803.5.11 Seismic Design Categories C through F Section 1803.5.12 Seismic Design Categories D through F Section 1808.7 Foundations on or Adjacent to Slopes Figure 1808.7.1 Foundation Clearances from Slopes Workbook page 54

73



74






Step 2. Review Flood Hazard Documentation Flood design class Elevation of proposed lowest floor, including basement Elevation nonresidential buildings will be Floodproofed Elevation of lowest horizontal structural member supporting a floor in Coastal High Hazard Areas.


77


Step 3. Review Tsunami Design Zone Maps The 2021 IBC and ASCE have specific provisions for several coastal areas defined tsunami inundation zones. If a project occurs within one of these inundation zones, they should ensure that the requirements of the state or local ordinances are being met in the design. If it is a Risk Category III or IV structure the IBC requires the design to also meet requirements of Chapter 6 in ASCE 7-16.







80










83








86





	Detailing Requirements	7 Section where Response System Deflection and 8 Regularments Modification Overstrength Amplification				Selsmic Design Catego			
	are Specified	Coefficient R ^a	Coverstrength Factor, (L ₀ f)	Amplification Factor, C ₂ ^p		Seism	nic Des	ign Cale	gory
	an specimen	Antiniana II	1900,14	. 1 01 00 00		c	D4	Ed	p.
A. BEARING WALL SYSTEMS								-	
1. Special reinforced concrete shear walls	14.2 and 14.2.3.6	. 5	21/2	.5	NL.	NL	160	160	100
 Ordinary reinforced concrete shear walls 	14.2 and 14.2.3.4	4	21/2	4	NŁ	NL	NP	NP	NP
3. Detailed plain concrete shear walls	14.2 and 14.2.3.2	2	21/2	2	NL.	NP	NP	NP	NP
4. Ordinary plain concrete shear walts	14-2 and 14-2-3-1	11/2	21/2	11/2	NL	NP	NP	NP	NP
5. Intermediate process shear walls	14.2 and 14.2.3.5	-4	21/2	4	NL.	NL.	40 ⁶	40 ^L	40 ⁴
6. Ordinary precast shear walls	14.2 and 14.2.3.3	- 3	21/2	3	NL	NP	NP	NP	NP
7. Special reinforced masonry shear walls.	14.4 and 14.4.3	5	21/2	31/2	NL	NL	160	160	100
 Intermediate reinforced masonry shear walls. 	14.4 and 14.4.3	31/2	21/2	21/4	NL	NL	NP	NP	NP
 Ordinary reinforced masonry shear walls 	34.4	2	21/2	13/4	NL	160	NP	NP	NP
10. Detailed plain masonry shear walls	14.4	2	21/2	154	NL	NP	NP	NP	NP.
1. Ordinary plain masonry shear walls	14.4	19	21/2	154	NL	NP	NP	NP	NP
2. Prestressed musonry shear walls	14.4	19	21/2	1%	NL	NP	NP	NP	NP
Light-framed walls sheathed with wood structural panels rated for shear resistance or steel sheets	14.1, 14.1.4.2, and 14.5	63/2	3	4	NL	NL.	65	65	65
 Light-framed walls with shear punels of all other materials 	14.1, 14.1.4.2, and 14.5	2	21/2	2	NL.	NL	35	NP	NP
 Light-framed will systems using flat- strap beacing 	14.1, 14.1,4.2, and 14.5	4	2	31/2	NL	NL	65	65	65

89


Step 2. Confirm geotechnical information
Soil Site Class Allowable Bearing Pressure Passive, Active and At-Rest Earth Pressures Structural Fill Requirements Soft soil or liquefaction mitigation measures (if applicable)
2011 IIC Performing Structural Plan Reviews Workbook page 72

Step 3. Verify material requirements • Appropriate Standards • Material Strengths • Appropriate Instructions • Extraneous Information **Extraneous Information** **Workbook page 73

91

Step 4. Review deferred submittal requirements • To be reviewed by design professional in responsible charge. • Design professional shall affix a notation that the deferred items are in general conformance with their design of the building. • They shall be submitted to B.O. for review. • Shall not be installed until approved by B.O.


92








95









98










101










104










107










110










113










116









119









122










125








128








131








134






IASK I – C	oncrete Construction Review	/				
Table 1808.8.1	Compressive Strength of Concrete or Grout					
Table 1808.8.2	Concrete Cover					
Section 1901.2	Plain and Reinforced Concrete					
Section 1901.3	Anchoring to concrete					
Section 1901.4	Composite structural steel and concrete structures					
Section 1904	Durability Requirements					
Section 1905	Modifications to ACI 318					
Section 1906.1	Plain Concrete Footings					
Section 1907	Minimum Slab Provisions					
Section 1908	Shotcrete					
ACI 318-19	Building Code Requirements for Structural	Concrete				


137






ep 1. Check	com	nr	ecciva	s ctror	σth	
.p 1. Clicck	COIII	Рι	CSSIV	. JUICI	guii	
	TWNW 19.7	. Lander	posure categori	as and classes		
	Campin	Chee		Couling		
		Jrc.		County on reposal to Sorregulation		
	Training and Marring (T) Author (S) for common city and	w	Compressors	Country imposed to Visitings and Binging and the well imposed proposed to water		
		32	Coorn is real in	(morgant/spring)		
		7.		of Expense in Volce		
		.33	viyeles with largers	Opposite to have led		
			(MA) Taylord, general formuse 1	District with		
		100	307 -00F	907-788		
		MI.	10-10/112	310/30710398		
		A1.	ER-607 c1/6	1160 S MOV - 11 (MIR)		
		জ	907 - 286	1-30° (4000)		
		10-		Construction and Construction		
		92		with water witters form.		
		TB-		second then remove		
		171		make keint e		
		(2	printed weeps of a alternative sale free	Aleman pala Aleman Son Arma Lon ware oracity or Son county		


140










143










146








149





Step 1. Check drawing information Size, section, material grade and location of all members Floor elevations Column centers and offsets Camber requirements for members Joining requirements for built-up members Permanent bracing, column stiffeners, column web doubler plates, bearing stiffeners in beams and girders, web reinforcement, openings for other trades and other special details Complete connection design

151












155










158










161









164









167

Step 6. Check force-transfer shear walls • Wall pier width ≥ 2 ft. • Full height wall segment at each end of wall. • Collectors for force-transfer shall be provided through the full length of the shear wall.






170







173

